

SLENDER BENDER™ Crosswalk Marker



ULTRA SLIM RAISED CURB AND MARKER

The QWICK KURB® Slender Bender Pedestrian Marker combines all the desirable features of a raised curb system with a single piece, double sided crosswalk marker. This unique hybrid design is especially effective to mark pedestrian crosswalks and islands with higher ADT. The raised curb profile of the Slender Bender Pedestrian Marker acts as a strong and noticeable warning for motorists to slow down and watch for pedestrians.

The single-piece, double sided Crosswalk Marker connects to the long base using the unique QWICK KURB two-part vertical rebounding flex boot support. This allows for installation of extra large 42 in. markers that can spring back to an upright position after an impact.

The Slender Bender base is only 10 5/8" wide so it easily fits within solid yellow median marker lines. In addition, the patented two-tiered profile of the curb is designed to keep the base stationary during a run over.

- **10 5/8" (270 mm) base width**
- **Lightweight - When installed unanchored, it can be easily deployed and retrieved for daily use operations.**
- **Two-tier profile is designed to keep base stationary during vehicle impacts**
- **Can be installed as an anchored or unanchored device**

SLENDER BENDER™ Pedestrian Marker



Base

Base Height
3 3/8 in. (86 mm)

Length
40 7/8 in. (1038 mm)

Width
10 5/8 in. (270 mm)

Weight
34 lb. (15.4 kg)

Available Base Colors
Yellow, White

Crosswalk Panel Marker

Combined Base and Marker Height
45 3/8 in. (1152 mm)

Width
8 5/8 in. (219 mm)

Depth
2 3/4 in. (70 mm)

Available MUTCD Messages
STOP, YIELD, Custom

Available Sheeting Colors
Amber, Fluorescent Green

Performance

MASH / NCHRP 350 Category
Category III

Anchored Performance
TL-3

Unanchored Performance
TL-1

Part Number
L54 (Base), L104 (Marker)

QWICK KURB®, Inc.

1916 US 41 South • Ruskin, FL 33570 • (813) 645-5072
www.qwickkurb.com

General details for QWICK KURB Systems are subject to change without notice to reflect improvements and upgrades. Always refer to the installation manual for details and cautions. Additional information is available from QWICK KURB, INC.
© QWICK KURB, INC.